

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 2020/878; US OSHA HCS 2015; and Canadian WHMIS 2015.

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** JP-K101
Product Name: JP-K101
X Code: X(22,53)1330
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- 1.3 Details of the Supplier of the Safety Data Sheet:**
Company Name: Hitachi Industrial Equipment & Solutions America, LLC
2730 Greenleaf Avenue **Phone Number:**
Elk Grove Village, IL 60007 (866)583-0048
Information: Christian Krzykwa (980)500-7144
- 1.4 Emergency telephone number:**
Emergency Contact: Chemtrec (800)424-9300

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
Flammable Liquids, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Skin Corrosion/Irritation, Category 2
Skin Sensitization, Category 1
Germ Cell Mutagenicity, Category 2
- 2.2 Label Elements:**

**GHS Signal Word:** **Danger****Hazard-determining components of labelling:**

2- Butonone

Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-

GHS Hazard Phrases:

H225 - Highly flammable liquid and vapor.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H336 - May cause drowsiness or dizziness.

H341 - Suspected of causing genetic defects.

GHS Precautionary Phrases:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

- P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P235 - Keep cool.

GHS Response Phrases:

- P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+313 - IF exposed or concerned: Get medical attention/advice.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P321 - Specific treatment see ... on this label.
P332+313 - If skin irritation occurs, get medical advice/attention.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P362+364 - Take off contaminated clothing and wash it before reuse.
P370+378 - In case of fire, use ... to extinguish.

GHS Storage and Disposal Phrases:

- P403+233 - Store container tightly closed in well-ventilated place.
P405 - Store locked up.
P501 - Dispose of contents/container to ...

UFI:

- 2.3 Adverse Human Health Hazards** not otherwise classified (HNOC) or not covered by GHS. Hazards not otherwise **Effects and Symptoms:** classified (HNOC) or not covered by GHS -none. ROUTE OF EXPOSURE: Multiple Routes: Harmful if swallowed, inhaled, or absorbed through skin.

Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
78-93-3	2- Butonone 01-2119457290-43-xxxx	60.0 -75.0 %	201-159-0 606-002-00-3	Flam. Liq. 2: H225 Eye Damage 2: H319 STOT (SE) 3: H336 EUH066
64-17-5	Ethyl alcohol 01-2119457610-43	4.765 -14.295 %	200-578-6 603-002-00-5	Flam. Liq. 2: H225
9004-36-8	Cellulose ester na	0.1 -1.0 %	NA NA	No GHS classifications apply.
2530-83-8	3-Glycidoxypropyltrimethoxysilane 01-2119513212-58	0.5 -5.0 %	219-784-2 NA	Eye Damage 1: H318
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylethoxy)propyl]- 01-2120120420-79	0.5 -5.0 %	220-780-8 NA	Skin Corr. 2: H315 Skin Sens. 1: H317 Eye Damage 2: H319 STOT (SE) 3: H335 Mutagen 2: H341

Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
- In Case of Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician. If inhaled, remove to fresh air. If breathing is difficult, give oxygen.
- In Case of Skin Contact:** Wash off with soap and plenty of water. Consult a physician.
- In Case of Eye Contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Assure adequate flushing of the eyes by separating the eyelids with fingers.
- In Case of Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. If swallowed, wash out mouth with water provided person is conscious. Call a physician.
- 4.2 Important Symptoms and Effects, Both Acute and Delayed:** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11 To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting.
- 4.3 Indication of any immediate medical attention and special treatment needed:** No data available.

Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. Suitable: Carbon dioxide, dry chemical powder, or appropriate foam.
- 5.2 Flammable Properties and Hazards:** Carbon oxides,
Flash back possible over considerable distance. Container explosion may occur under fire conditions. No data available.
No data available.
- Flash Pt:** > -2.99 C Method Used: Estimate
- Explosive Limits:** LEL: No data. UEL: No data.
- Autoignition Pt:** ~ 365.00 C
- 5.3 Fire Fighting Instructions:** Wear self contained breathing apparatus for fire fighting if necessary. Further information. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Emits toxic fumes under fire conditions.

Section 6. Accidental Release Measures

- 6.1 Protective Precautions, Protective Equipment and Emergency Procedures:** Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.
- 6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
- 6.3 Methods and Material For Containment and Cleaning Up:** Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. PROCEDURE TO BE FOLLOWED IN

CASE OF LEAK OR SPILL. Evacuate area. PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear self-contained breathing apparatus, rubber boots, and heavy rubber gloves.

Methods for cleaning up.

Cover with dry lime or soda ash, pick up, keep in a closed container, and hold for waste disposal.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2. User Exposure: Do not breathe vapor. Do not get in eyes, on skin, on clothing.
- 7.2 Precautions To Be Taken in Storing:** Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic.
Storage class 510) Recommended storage temperature: 2 -8 - 8 deg.C.
Handle and store under inert gas. Storage class 510): Combustible liquids Non Combustible. Suitable: Keep tightly closed. Store in a cool, dry place.
- Other Precautions:** Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
78-93-3	2- Butonone	ACGIH TLV	TLV: 200 ppm STEL: 300 ppm	
		Europe	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	
		France VL	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	
		OSHA PELs	PEL: 200 ppm	
		Britain EH40	TWA: 600 mg/m3 (200 ppm) STEL: 899 mg/m3 (300 ppm)	Skin Absorption
64-17-5	Ethyl alcohol	ACGIH TLV	TLV: 1000 ppm STEL: 1000 ppm	
		France VL	TWA: 1900 mg/m3 (1000 ppm) STEL: 9500 mg/m3 (5000 ppm)	
		OSHA PELs	PEL: 1000 ppm	
		Britain EH40	TWA: 1920 mg/m3 (1000 ppm) STEL: ()	

8.2 Exposure Controls:

- 8.2.1 Engineering Controls (Ventilation etc.):** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Use only in a chemical fume hood. Safety shower and eye bath.

8.2.2 Personal protection equipment:

- Eye Protection:** Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles. Faceshield (8-inch minimum).
- Protective Gloves:** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Splash contact:
Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 292 min.
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario. Full contact.
Material: Nitrile rubber, Minimum layer thickness: 0.4 mm, Break through time: 480 min.
Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min.
- Other Protective Clothing:** Impervious clothing. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Complete suit protecting against chemicals.
- Respiratory Equipment (Specify Type):** Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Other: Wear appropriate government approved respirator, chemical-resistant gloves, safety goggles, other protective clothing.
- Work/Hygienic/Maintenance Practices:** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse. Discard contaminated shoes.
- 8.2.3 Environmental Exposure Controls:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
- Exposure Scenarios:** No data available.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

- Physical States:** [] Gas [X] Liquid [] Solid
- Appearance and Odor:** liquid. Color: Dark solvent odor.
- pH:** No data.
- Melting Point:** -86.99 C
- Boiling Point:** 78.00 C - 126.00 C
- Flash Pt:** > -2.99 C Method Used: Estimate
- Evaporation Rate:** No data.
- Saturated Vapor Concentration:** No data.

Flammability (solid, gas):	No data available.	
Explosive Limits:	LEL: No data.	UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.	
	No data.	
Vapor Density (vs. Air = 1):	> Air	
Specific Gravity (Water = 1):	0.8327	
Density:	~ 0.8628 G/ML (~ 7.2 - LB/GA)	
Solubility in Water:	miscible	
Octanol/Water Partition Coefficient:	No data.	
Autoignition Pt:	~ 365.00 C	
Decomposition Temperature:	No data.	
Viscosity:	No data.	
Explosive Properties:	No data available.	
Oxidizing Properties:	No data available.	

9.2 Other Information

9.2.1 Information with regard to physical hazard classes

Information with regard to primary physical hazard:

9.2.2 Other safety characteristics

Section 10. Stability and Reactivity

10.1 Reactivity:	No data available.
10.2 Stability:	Unstable [] Stable [X]
10.3 Conditions To Avoid - Hazardous Reactions:	Vapors may form explosive mixture with air. No data available.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
10.4 Conditions To Avoid - Instability:	Exposure to moisture. Heat, flames and sparks. Extremes of temperature and direct sunlight. No data available.
10.5 Incompatibility - Materials To Avoid:	Oxidizing agents, Strong reducing agents, Strong oxidizing agents. Acid anhydrides, Aluminum, Halogenated compounds, Acids. Oxidizing agents. Strong oxidizing agents, Bases.
10.6 Hazardous Decomposition or Byproducts:	No data available. In the event of fire: see section 5. Other decomposition products: HAZARDOUS DECOMPOSITION PRODUCTS. -Carbon oxides. silicon oxides, Reacts with water to form methanol. Methanol is given off during processing and by reaction with water. Carbon monoxide.

Section 11. Toxicological Information

11.1 Information on Toxicological Effects:

Acute toxicity.

Germ cell mutagenicity. No data available.

Reproductive toxicity. Aspiration hazard: Inhalation: Dermal.

CAS# 78-93-3:

Acute toxicity, LD50, Intraperitoneal, Mouse, 616.0 MG/KG.

Result:

Lungs, Thorax, or Respiration: Sputum.

Biochemical: Metabolism (Intermediary): Other proteins.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

- Shell Chemical Company. Unpublished Report., Vol/p/yr: -,6, 1961

Acute toxicity, LD50, Skin, Species: Rabbit, 6480. MG/KG.

Result:

Lungs, Thorax, or Respiration:Other changes.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

- Shell Chemical Company., Vol/p/yr: MSDS-5390-,

Acute toxicity, LC50, Inhalation, Mouse, 32.00 MG/M3.

Result:

Brain and Coverings: Other degenerative changes.

Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

Acute toxicity, LD50, Intraperitoneal, Species: Guinea pig, 2.000 GM/KG.

Result:

Immunological Including Allergic: Increase in humoral immune response.

Irritation or Corrosion: Skin corrosion/irritation.

Result: Tumorigenic:Tumors at site or application. No skin irritation . (OECD Test Guideline 404) Serious eye damage/eye irritation Eyes -Rabbit)

Irritating to eyes . No data available. Serious eye damage/eye irritation no data available.

Provide adequate ventilation.

Mild eye irritation Serious eye damage/eye irritation Eyes -rabbit. Serious eye damage/eye irritation: Eyes - rabbit -

Eyes: Rabbit.

Sensitization: No data available.

Chronic Toxicological Effects:

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity -repeated exposure: no data available. Specific target organ toxicity -single exposure (Globally Harmonized System) No data available.

Inhalation. Oral. Specific target organ toxicity - repeated exposure:

Carcinogenicity/Other Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. IARC: 3 -Group 3: Not classifiable as to its carcinogenicity to humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
78-93-3	2- Butonone	n.a.	n.a.	n.a.	n.a.
64-17-5	Ethyl alcohol	n.a.	1	A4	n.a.
9004-36-8	Cellulose ester	n.a.	n.a.	n.a.	n.a.
2530-83-8	3-Glycidoxypropyltrimethoxysilane	n.a.	n.a.	n.a.	n.a.
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-	n.a.	n.a.	n.a.	n.a.

Section 12. Ecological Information

- 12.1 Toxicity:** No data available.
- 12.2 Persistence and Degradability:** No data available. Biodegradability Result: - - Readily biodegradable.
- 12.3 Bioaccumulative Potential:** No data available.
- 12.4 Mobility in Soil:** No data available.
- 12.5 Results of PBT and vPvB assessment:** PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.
- 12.6 Other adverse effects:** No data available. Harmful to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

- 13.1 Waste Disposal Method:** Product.
Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Contaminated packaging. APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Section 14. Transport Information

- GHS Classification:** Flammable Liquids, Category 2 - Danger! Highly flammable liquid and vapor
Specific Target Organ Toxicity (single exposure), Category 3 - Warning! May cause respiratory irritation, or may cause drowsiness and dizziness
Skin Corrosion/Irritation, Category 2 - Warning! Causes skin irritation
Skin Sensitization, Category 1 - Warning! May cause an allergic skin reaction
Germ Cell Mutagenicity, Category 2 - Warning! Suspected of causing genetic defects

14.1 LAND TRANSPORT (US DOT):

- DOT Proper Shipping Name:** Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
- DOT Hazard Class:** 3 FLAMMABLE LIQUID
- UN/NA Number:** UN1210 II



14.1 LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
UN Number: 1210 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID **TDG Classification:**

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
UN Number: 1210 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
UN Number: 1210 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	2- Butonone	No	Yes NA	No
64-17-5	Ethyl alcohol	No	No	No
9004-36-8	Cellulose ester	No	No	No
2530-83-8	3-Glycidoxypropyltrimethoxysilane	No	No	No
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-	No	No	No

CAS #	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
78-93-3	2- Butonone	Yes: Part 5	No	Yes
64-17-5	Ethyl alcohol	Yes: Part 5		Yes
9004-36-8	Cellulose ester	No	No	Yes
2530-83-8	3-Glycidoxypropyltrimethoxysilane	No	No	Yes
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-	No	No	Yes - N: Part 1

California Proposition 65



WARNING

This product can expose you to chemicals including .alpha.-Methyl styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
78-93-3	2- Butonone	TSCA: Yes - Inventory; CA PROP.65: No
64-17-5	Ethyl alcohol	TSCA: Yes - Inventory; CA PROP.65: No
9004-36-8	Cellulose ester	TSCA: Yes - Inventory; CA PROP.65: No
2530-83-8	3-Glycidoxypropyltrimethoxysilane	TSCA: Yes - Inventory, 8A; CA PROP.65: No
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-	TSCA: Yes - Inventory, 8A; CA PROP.65: No

CAS #	Hazardous Components (Chemical Name)	International Regulatory Lists
78-93-3	2- Butonone	Mexico INSQ: Yes - 1193; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 2-542; Japan ISHL: No; Korea ECL: Yes - KE-24094; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel

64-17-5	Ethyl alcohol	HSL: No; Germany WHCS: Yes - 150: WGK 1; Switzerland Giftliste 1: Yes - G-2429; Switzerland INNS: No; REACH: Yes - 01-2119457290-43: Full, (P)
9004-36-8	Cellulose ester	Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 5-153; Japan ISHL: No; Korea ECL: Yes - KE-13217; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: Yes - Cat.; Germany WHCS: Yes - 96: WGK 1; Switzerland Giftliste 1: Yes - G-1158; Switzerland INNS: No; REACH: Yes - 01-2119457610-43: Full, (P)
2530-83-8	3-Glycidoxypropyltrimethoxysilane	Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 8-168; Japan ISHL: No; Korea ECL: Yes - KE-05342; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: No; Germany WHCS: Yes - 7208: WGK 0/nwg; Switzerland Giftliste 1: Yes - G-8394; Switzerland INNS: No; REACH: Yes - (P)
2897-60-1	Silane, Diethoxymethyl[3-(oxiranylmethoxy)propyl]-	Mexico INSQ: No; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 2-2962; Japan ISHL: No; Korea ECL: Yes - KE-34368; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: No; Germany WHCS: Yes - 2622: WGK 2; Switzerland Giftliste 1: No; Switzerland INNS: No; REACH: Yes - 01-2119513212-58: Full, (P)
		Mexico INSQ: No; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 2-2072; Japan ISHL: No; Korea ECL: KE-14-0113; Philippines ICCS: No; Taiwan TCSCA: Yes; Singapore HSL: No; Israel HSL: No; Germany WHCS: No; Switzerland Giftliste 1: No; Switzerland INNS: No; REACH: Yes - 01-2120120420-79: Full, (P)

Section 16. Other Information

Revision Date: 03/07/2022

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information and recommendations contained herein are, to the best of Hitachi's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, HITACHI recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by Hitachi hereunder are given gratis and Hitachi assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.